

Test Requirement:

According to the requirement of the Module C2 (SPC CE-062_EN M4 PPE) of Applus+, the test item(s) of the sample is according to the standard EN149:2001+A1:2009.

Product:	PROTECTIVE BUTTERFLY MASK						
Report No.:	PTC21020200501C-EN01						
APPLUS +With ID number:							
Client:	The Purples						
Client Address:							
Manufacturer:	Zhejiang The Purples						
Manufacturer Address:							
Contact:	Jiang lihua						
Model(s):	Q3						
Classification:	FFP3 NR						
Date of Tests:	2021.02.02~2021.02.06						
Signed for and on Behalf of PTC							
Prepare by:	Checked by:	Approved by:					

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

Tim Mo



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 2 of 13

Summary of assessment

Clause	Assessment
7.3 Visual inspection	PASS
7.5 Material	PASS
7.9.1 Total inward leakage	PASS
7.9.2 Penetration of filter material	PASS
7.12 Carbon dioxide content of the inhalation air	PASS
7.16 Breathing resistance	PASS
7.18 Demountable parts	PASS

Remark:

PASS: comply with requirement of standard



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 3 of 13

Test Result:

Requirement	Test Result	Conclusion
7.3 Visual inspection The visual inspection shall also include the marking and the information supplied by the manufacturer.	Comply	Pass
7.5 Material Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	No mechanical failure after	

Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.

After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps.

When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse.

failure after
undergoing the
conditioning
described in
8.3.1,
No collapse when
conditioned in
accordance with
8.3.1 and 8.3.2.

7.9.1 Total inward leakage

For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than 25 % for FFP1, 11 % for FFP2, 5 % for FFP3 and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than 22 % for FFP1, 8 % for FFP2, 2 % for FFP3.

FFP3, Test
results are
shown in Annex
A Table
7.9.1-A&B

7.9.2 Penetration of filter material

The penetration of the filter of the particle filtering half mask shall meet the requirements of Table 1.

	Sodium chloride test	Paraffin oil test 95
	95 l/min	l/min
FFP1	≤ 20%	≤ 20%
FFP2	≤ 6%	≤ 6%
FFP3	≤ 1%	≤ 1%

FFP3 , Test
results are
shown in Annex
A Table 7.9.2.



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 4 of 13

7.12 Carbon dioxide content of the inhalation air

The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1,0 % (by volume)

Test results are shown in Annex A Table 7.12.

Pass

7.16 Breathing resistance

	Maximun	n permitted resist	esistance (mbar)				
Classification	Inhal	Exhalation					
	30 l/min	95 l/min	160 l/min				
FFP1	0.6	2.1	3.0				
FFP2	0.7	2.4	3.0				
FFP3	1.0	3.0	3.0				

FFP3. Test results are shown in Annex A Table 7.16.

Pass

7.18 Demountable parts

All demountable parts (if fitted) shall be readily connected and secured, where possible by hand

Comply

Pass



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 5 of 13

Annex A: Summarization of Test Data

Table 7.9.1-A: Inward Leakage Test Data

Test specification: EN 149:2001+A1:2009 Clause 8.5

Subject	Sample No.	Condition	Walk (%)	Head Side/side (%)	Head up/down (%)	Talk (%)	Walk (%)	Mean (%)
Lv	1	A.R	1.1	1.2	1.3	1.4	1.2	1.2
Li	2	A.R	1.1	1.3	1.5	1.3	1.2	1.3
Zhong	3	A.R	1.4	1.5	1.3	1.3	1.2	1.3
Xu	4	A.R	1.6	1.4	1.8	1.2	1.5	1.5
Ма	5	A.R	1.2	1.3	1.4	1.5	1.5	1.4
Chen	6	T.C	1.0	1.2	1.0	1.2	1.3	1.1
Chen	7	T.C	1.3	1.4	1.4	1.2	1.2	1.3
Zhuo	8	T.C	1.1	1.0	1.3	1.8	1.6	1.4
Chen	9	T.C	1.5	1.1	1.3	1.5	1.5	1.4
Zhang	10	T.C	1.2	1.3	1.1	1.5	1.2	1.3

Table 7.9.1-B: Facial dimension

Subject	Face Length	Face Width	Face Depth	Mouth Width
Lv	113	139	104	53
Li	120	135	112	55
Zhong	108	135	106	56
Xu	120	150	120	70
Ma	130	170	130	80
Chen	110	160	90	40
Chen	115	145	110	50
Zhuo	103	146	100	50
Chen	110	145	95	40
Zhang	144	141	101	54



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 6 of 13

Table 7.9.2: Penetration of filter material

Test specification: EN 149:2001+A1:2009 Clause 8.11

Aerosol	Condition	Sample No.	Penetration (%)	Assessment
		11	0.2	
	As received			
		As received 12 0.2 13 0.2		
		14	0.1	
Sodium chloride test	Simulated wearing treatment	15	0.2	
		16	0.2	
		17	0.1	
Paraffin oil test	Mechanical strength + Temperature conditioned	18	0.1	
	remperature conditioned	19	0.1	
		20	0.1	Pass
	As received	21	0.1	
		22	0.1	
		23	0.1	
	Simulated wearing treatment	24	0.1	
		25	0.1	
		26	0.1	1
	Mechanical strength + Temperature conditioned	27	0.1	1
	remperature conditioned	28	0.1	1

Table 7.12: Carbon dioxide content of the inhalation air

Test specification: EN 149:2001+A1:2009 Clause 8.7

Condition	Sample No.	Resu	ult (%)	Assessment
	29	0.04	Magazakia	
As received	30	0.04	Mean value:	Pass
	31	0.04	0.04	



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 7 of 13

Table 7.16: Breathing resistance (mbar)

Test specification: EN 149:2001+A1:2009 Clause 8.9

-	Flow Ra		32			33			34									
	30		0.30				0.28				0.30							
As received	Inhalation	95 I/min			1.17					1.14			1.12					
	Exhalation	160	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е	
	Lanatation	l/min	1.78	1.84	1.78	1.77	1.80	1.79	1.77	1.77	1.80	1.76	1.76	1.75	1.81	1.76	1.73	
	Flow Ra	ate		35					36					37				
Simulated	Inhalation 30 I/min 95 I/min		0.29			0.29				0.31								
wearing treatment							0.97				1.02							
treatment	Exhalation 160 l/min	160	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е	
		Extidiation	LAHalation	l/min	1.40	1.43	1.44	1.44	1.41	1.39	1.39	1.43	1.43	1.39	1.41	1.37	1.43	1.44
	Flow Ra	ate			38			39					40					
Temperature	Inhalation	30 I/min			0.28			0.28				0.28						
conditioned	innaiation	95 I/min			0.97					0.98					0.97			
	Evhalatica	160	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е	
	Exhalation	l/min	1.40	1.39	1.37	1.37	1.40	1.36	1.40	1.35	1.35	1.35	1.38	1.34	1.41	1.42	1.41	
Assessment								Pa	ss									

A: Facing directly ahead C: Facing vertically downwards B: Facing vertically upwards


D: Lying on the left side E: Lying on the right side



Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 8 of 13

Test	Uncertainty			
Total inward leakage	3.8%			
Penetration of filter material(NaCl)	3.5%			
Penetration of filter material(Paraffin oil)	4.2%			
Carbon dioxide content of the inhalation air	4.5%			
Breathing resistance(30L/min)	5.2%			
Breathing resistance(95L/min)	5.4%			
Breathing resistance(160)L/min)	6.0%			


Photo(s) of Sample:





Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 9 of 13







Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 10 of 13







Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 11 of 13








Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 12 of 13







Report No.:PTC21020200501C-EN01 Issue Date: Feb.06, 2021 Page 13 of 13



End of Report